

DRILLING LOG		DIVISION		INSTALLATION		Hole No. CB-ND-2	
		South Atlantic		Jacksonville District		SHEET 1 OF 1 SHEETS	
1. PROJECT North Dade County Beach Erosion Control				10. SIZE AND TYPE OF BIT N/A			
2. LOCATION (Coordinates or Station) X=797,784 Y=594,458				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MSL			
3. DRILLING AGENCY Corps of Engineers				12. MANUFACTURER'S DESIGNATION OF DRILL Vibracore			
4. HOLE NO. (As shown on drawing title and file number) CB-ND-2				13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN		DISTURBED UNDISTURBED	
5. NAME OF DRILLER R. Gordon				14. TOTAL NUMBER CORE BOXES			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT.				15. ELEVATION GROUND WATER Tidal		16. DATE HOLE STARTED 14 Jun 78 COMPLETED 14 Jun 78	
7. THICKNESS OF OVERBURDEN				17. ELEVATION TOP OF HOLE -55.0		18. TOTAL CORE RECOVERY FOR BORING 100 %	
8. DEPTH DRILLED INTO ROCK				19. Geologist: D. Rosen			
9. TOTAL DEPTH OF HOLE 3.3'							

ELEVATION a	DEPTH b	LEGEND c	CLASSIFICATION OF MATERIALS (Description) d	% CORE RECOVERY e	SAMPLE NO. f	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g
-55.0	0.0					BIT OR BARREL
-58.3	3.3		SAND, light gray, medium, shell sand (SP)		1	VIBRACORE
<p>NOTE: This vibracore boring was drilled with equipment of unproven performance. It is believed the shallow refusal depth of this boring is not solely due to the physical character of the sediments encountered.</p> <p>Although the datum for this core boring is marked "MSL", it is likely the actual datum was M.L.W. There is 1.3 foot difference between M.S.L. and M.L.W.</p>						
						LABORATORY CLASSIFICATION: SAMPLE NO. 0-3.3' LAB CLASS. (SP)