

DRILLING LOG		DIVISION		INSTALLATION		SHEET	
PROJECT		South Atlantic		Jacksonville District		OF 1 SHEET	
1. PROJECT		North Dade County B.F.C.		10. SIZE AND TYPE OF BIT		see remarks	
2. LOCATION (Coordinates or Station)		X=797.937 Y=592.353		11. DAYUM FOR ELEVATION SHOWN (TBM or MLL)		MLW	
3. DRILLING AGENCY		Oceanprobe, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL		Exmar Hydraulic Vibracore	
4. HOLE NO. (As shown on drawing title and file number)		CB-ND-36		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN		DISTURBED	
5. NAME OF DRILLER		B. Barth		14. TOTAL NUMBER CORE BOXES		2	
6. DIRECTION OF HOLE		<input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER		Tidal +3.1	
7. THICKNESS OF OVERBURDEN				16. DATE HOLE		STARTED 12-5-83 COMPLETED 12-5-83	
8. DEPTH DRILLED INTO ROCK				17. ELEVATION TOP OF HOLE		-58.9	
9. TOTAL DEPTH OF HOLE		20.0 ft.		18. TOTAL CORE RECOVERY FOR BORING		78	
				19. SIGNATURE OF INSPECTOR		GEOLOGIST T. Novak	
ELEVATION	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	% CORE RECOVERY	BOX OR SAMPLE NO.	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant)	
-58.9	0.0					Bit or Barrel	
-60.0	1.1	<	SAND, fine to medium, quartz shell with calcium carbonates, predominantly fine grain, slightly silty, light gray (SP)	4.9	1	3" Barrel	
		I	Numerous coral with sandstone fragments up to 1 inch in diameter from -60.0 to -66.7				
-66.7	7.8	I		4.9		-63.8 Cut	
		I					
-72.1	13.2	I		4.9	2	-68.7 Cut	
-72.6	13.7	I	CORAL with SANDSTONE from -72.1 to -72.6				
-73.8	14.9	I	Cemented Sand, friable from -72.6 to -73.8 buff in color	0.5		-73.6 Cut	
		I	Loose Sand (SP) from -73.8 to -78.9	0.3		-74.1 " Cut	
-78.9	20.0					-74.4 Bit Sample	
						LABORATORY CLASSIFICATION	
						SAMPLE LAB	
						NO. CLASS.	
						#1 60.0-60.5 (SP)	
						#2 68.0-68.7 (SP-SM)	