

DRILLING LOG			DIVISION South Atlantic		INSTALLATION Jacksonville District		SHEET 1 OF 1	
1. PROJECT DADE COUNTY SPP					10. SIZE AND TYPE OF BIT 3 1/2" Drive Shoe			
2. LOCATION (Coordinates of Station) X=79757.18 Y=50050.8.0					11. DATUM FOR ELEVATION FROM (TBM or NSL) MLW			
3. DRILLING AGENCY ALPINE OCEAN SURVEY, INC.					12. MANUFACTURER'S DESIGNATION OF DRILL VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) CB-DAC-177					13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER NICK PRICE					14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED					15. ELEVATION GROUND WATER Tide = +1.8			
7. THICKNESS OF BURDEN 0 Ft.					16. DATE HOLE STARTED COMPLETED 7/4/98 0859/0901			
8. DEPTH DRILLED INTO ROCK 0 Ft.					17. ELEVATION TOP OF HOLE -32.8 Ft.			
9. TOTAL DEPTH OF HOLE 19.9 Ft.					18. TOTAL CORE RECOVERY FOR BORING 89 %			
19. SIGNATURE OF GEOLOGIST ROCKLAND BURR								
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS		
-32.8	0		Sand, fine to medium grained, light brown, a little shell fragments (SP)			-32.8	0	
						Lat-Lon 25 42 28.3W 80 05 47.0W Laboratory Data Depth USCS SpG. 3.5 SP 8.5 SP-SM 10.5 SP-SM 12.0 SM	2.5	
-40.6	8.0		Sand, fine grained, light brown, trace of shell fragments (SP-SM)				7.5	
-42.0	10.0		Sand, fine to medium grained, light brown, some shell fragments (SP-SM)				10	
-43.5	10.9		Silty sand, fine grained, light brown, few shell fragments (SM)				12.5	
							15	
							17.5	
-52.5	19.8		End of Boring				20	
			Soils are field visually classified in accordance with the Unified Soils Classification System.				22.5	