

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Palm Beach County Vibracore 2004 Palm Beach County, Florida			9. SIZE AND TYPE OF BIT 4.0 In.	
2. BORING DESIGNATION BB04-29			10. COORDINATE SYSTEM/DATUM Florida State Plane East	
3. DRILLING AGENCY Alpine OSS, Inc.			11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER SEA INC			12. TOTAL SAMPLES 5	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			13. TOTAL NUMBER CORE BOXES 2	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			14. ELEVATION GROUND WATER	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			15. DATE BORING 05-25-04	
8. TOTAL DEPTH OF BORING 19.3 Ft.			16. ELEVATION TOP OF BORING -24.1 Ft.	
			17. TOTAL RECOVERY FOR BORING 19.3 Ft.	
			18. SIGNATURE AND TITLE OF INSPECTOR Gary Zarillo PG	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	REMARKS
-24.1	0.0					
			Gray (10YR-6/1), Gray fine quartz sand, some medium to fine carbonate sand, (SP).		0.5	Sample #0.5, Depth = 0.5
-28.5	4.4				4.0	Sample #4.0, Depth = 4.0
			Gray (10YR-6/1), Gray fine quartz sand, coarse to fine carbonate sand, white to gray shell fragments and whole shells in fine to medium gravel range, (SP).		8.0	Sample #8.0, Depth = 8.0
-34.1	10.0				12.0	Sample #12.0, Depth = 12.0
			(10YR-6.5/1), Gray fine quartz sand, some coarse to fine carbonate sand, (SP).		15.0	Sample #15.0, Depth = 15.0
-41.0	16.9					
-41.9	17.8		(10YR-6.5/2), Brownish gray fine quartz sand, coarse to fine carbonate sand, gray shell fragments in fine to medium gravel range, (SP).			
-43.4	19.3		Light brownish gray (10YR-6/2), Brownish gray fine quartz sand, (SP).			
			End of Boring		Comp	Sample #Comp, Depth = 19.0 Composite 0-15.0 ft.

FLORIDA DEP ROSS BRINY BREEZES.GPJ FL DEP ROSS.GDT 11/12/04