

DRILLING LOG	DIVISION South Atlantic	INSTALLATION Jacksonville District	<i>SHEET 1 OF 1</i>
1. PROJECT Nassua County Beach Nourishment		10. SIZE AND TYPE OF BIT See Remarks	
2. LOCATION (Coordinates or Station) X=740,,710, Y=250,,188		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW (FEET)	
3. DRILLING AGENCY Corps of Engineers		12. MANUFACTURER'S DESIGNATION OF DRILL Failing 1500	
1. HOLE NO. (As shown on drawing title and file number) CB-NC92-2A		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 9 undisturbed: 0	
5. NAME OF DRILLER Mark Whitson		14. TOTAL NUMBER OF CORE BOXES 1	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER TIDAL	
7. THICKNESS OF BURDEN Ft.		16. DATE HOLE STARTED COMPLETED 9/8/92 9/8/92	
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -19.6 Ft.	
9. TOTAL DEPTH OF HOLE 15 Ft.		18. TOTAL CORE RECOVERY FOR BORING 50 %	
		19. SIGNATURE OF GEOLOGIST Robert Ross	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS Bit or Barrel	BLOWS/ft
-19.6	.0					-19.6	
			Sand, fine to medium quartz, trace of sand sized shell, gray (SP)	48	1	2" SAMPLER	6 15 17 20
-23.6	4.0		CLAY, sandy, gray (CH)		2		30
-24.6	5.0		SAND, fine to medium quartz, gray (SP-SC)		3		2
-25.6	6.0		SAND, some clay, gray (SC)		4		2
-26.6	7.0		SAND, fine to medium quartz, gray (SP-SC)	48	5	2" SAMPLER	3 6
-28.6	9.0		CLAY, sandy, gray (CH)		6		6
-29.6	10.0		SAND, fine to medium quartz, gray (SP)		7		2
-30.6	11.0		SAND, fine to medium quartz, some clay to clayey, gray (SC)		8		2
-32.6	13.0		SAND, fine to medium quartz, trace sand sized shell, gray (SP)	54	9	2" SAMPLER	31 44
-34.6	15.0		2 inch (CH) bed at -34 feet			-34.6	36
			NOTE: Soils are field visually classified in accordance with the Unified Soils Classification System. Samples recovered using a 2 inch (I.D.) sampler, 5 feet long, driven with a 300 pound hammer, 18 inch drop				