

Hole No.CB-NC93-32

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Jacksonville District		SHEET 1 OF 1	
1. PROJECT Nassau County beach nourishment				10. SIZE AND TYPE OF BIT See Remarks			
2. LOCATION (Coordinates or Station) X=249,821 Y=737,502				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW (FEET)			
3. DRILLING AGENCY Corps of Engineers				12. MANUFACTURER'S DESIGNATION OF DRILL Failings 314			
4. HOLE NO. (As shown on drawing title and file number) CB-NC93-32				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0			
5. NAME OF DRILLER D. Justiss				14. TOTAL NUMBER OF CORE BOXES 1			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER TIDAL			
7. THICKNESS OF BURDEN Ft.				16. DATE HOLE STARTED COMPLETED 3/9/93 3/9/93			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -16.1 Ft.			
9. TOTAL DEPTH OF HOLE 15 Ft.				18. TOTAL CORE RECOVERY FOR BORING 81% %			
				19. SIGNATURE OF GEOLOGIST J. Aurthur			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS Bit or Barrel	BLOWS/ ft
-16.1	0		Sand, fine to medium, gray (SP)		1		3
				82	2	5' SPOON	4
-21.1	5.0		below -21.1, shelly				6
							7
-22.9	6.8		Sand, fine, silty, trace of clay, dark gray (SM)		3		12
				82	4	5' SPOON	SETTLED
-26.1	10.0		below -26.1, some clay				2
							1
							2
							SETTLED
							SETTLED
				80	5	5' SPOON	6
-31.1	15.0						2
							3
			NOTE: Soils are field visually classified in accordance with the Unified Soils Classification System.			300# HAMMER WITH 18" DROP USED ON 5.0' SOLID SPOON (2" I.D. X 2" 1/2 O.D.)	
			SAMPLE ELEVATION LABORATORY CLASSIFICATION				
			-16.1 to -18.2 (SP)				
			-22.9 to -24.3 (SM)*				
			NOTE: * Classification based on Gradation Curve. No Atterberg Limits.				