

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT South Amelia Island Shoreline Stabilization				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=372971.00 Y=2245841.800				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) A-30R2				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER J. Cole/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 4-16-01 4-19-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -8.9 Ft.			
9. TOTAL DEPTH OF HOLE 20.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-8.9	.0					-8.9	0
							2.5
							5
							7.5
-19.1	10.2						10
-20.0	11.1				11.0		
			White fine quartz sand, pale brown to white whole shells in medium gravel range. 10 YR 8.5/0.5 (SP)	100	13.0		12.5
-23.3	14.4		Light gray fine quartz sand, few scattered shell fragments and whole shells in coarse sand to medium gravel range. 10 YR 8/1 (SP)			-23.9	15
-24.9	16.0						
-25.2	16.3						
-26.0	17.1		Light gray fine quartz sand, abundant gray to white shell fragments and whole shells in fine to medium gravel range. 10 YR 8/1 (SP)	100			17.5
			Gray plastic mud. 10 YR 5/1 (CL)				
			Light gray fine quartz sand, very abundant gray shell fragments and whole shells in fine to coarse gravel range. 10 YR 7.5/0.5 (SW)			-29.0	20
-29.0	20.1		Light gray fine quartz sand, scattered gray to white shell fragments and whole shells in medium to coarse gravel range. 10 YR 8/0.5 (SP)			Composite 10.2-14.0 ft.	22.5