

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT South Amelia Island Shoreline Stabilization				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=371421.200 Y=2246231.400				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) A-26R2				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0			
5. NAME OF DRILLER J. Cole/E. Olsen				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 4-16-01 4-19-01			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -9.8 Ft.			
9. TOTAL DEPTH OF HOLE 18.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-9.8	.0					-9.8	0
							2.5
							5
							7.5
-17.8	8.0		Light gray to white fine quartz sand, abundant gray, light gray and white shell fragments in medium sand to coarse gravel range. 10 YR 8/0.5-8.5/0.5 (SP)		9.0		10
					11.0		12.5
-22.5	12.7			100			15
-22.9	13.1		Gray plastic mud. 10 YR 5/1 (CL)				17.5
-24.4	14.6		Light gray fine quartz sand, light gray to gray shell fragments and whole shells in medium gravel range. 10 YR 7.5/0.5 (SP)				20
			Brownish gray silty sand, scattered light gray to pale brown whole shells and shell fragments. 10 YR 6/3 (SM)	100		-24.6	22.5
				100			
-27.8	18.0					-27.8	
Composite 8.0-12.0 ft.							