

DRILLING LOG	DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT South Amelia Island Shoreline Stabilization		10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=373020.400 Y=2245848.400		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLLW	
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) A-30R1		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 5 undisturbed: 0	
5. NAME OF DRILLER J. Cole/E. Olsen		14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 4-16-01 4-19-01	
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -10.0 Ft.	
9. TOTAL DEPTH OF HOLE 15.8 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %	
		19. SIGNATURE OF G. Zarillo, SEA, Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-10.0	0					-10.0	0
			White fine quartz sand, scattered light gray to white shell fragments in coarse sand to medium gravel range. 10 YR 8.5/0.5 (SP)	100	0.5 3.0		2.5
-15.1	5.1		Light gray fine quartz sand, trace of shell fragments in coarse sand to fine gravel range. 10 YR 8/1 (SP)	100	6.0 10.0	-15.0 -20.0	5 10
				100	14.0		12.5
-25.0	15.0		Light gray fine quartz sand, abundant gray to white shells fragments in medium gravel range. 10 YR 7.5/0.5 (SP)			-25.8	15
-25.8	15.8						17.5
							20
						Composite 0-15.0 ft.	22.5