

DRILLING LOG		DIVISION SOUTH ATLANTIC		INSTALLATION MOBILE DISTRICT		Hole No. V-25-94 SHEET 1 OF 2 SHEETS	
1. PROJECT BAY CO FL OFFSHORE PANAMA CITY BEACHES NOURISHMENT				10. SIZE AND TYPE OF BIT 3.5" x 25' VIBRACORE			
2. LOCATION (Coordinates or Station) ZONE FLN: N 453042 E 1547125				11. ELEVATION DATUM NGVD, FOOT U.S. COORDINATE DATUM STATE PLANE, NAD27, FOOT U.S.			
3. DRILLING AGENCY TET, INC.				12. MANUFACTURER'S DESIGNATION OF DRILL VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) V-25-94				13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN 8		UNDISTURBED 0	
5. NAME OF DRILLER CHARLIE WESTON				14. TOTAL NUMBER CORE BOXES 0			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED DEG. FROM VERTICAL				15. ELEVATION GROUNDWATER			
7. THICKNESS OF OVERBURDEN -				16. DATE HOLE STARTED 28 NOV 94 COMPLETED 28 NOV 94			
8. DEPTH DRILLED INTO ROCK -				17. ELEVATION TOP OF HOLE EL. -30.5			
9. TOTAL DEPTH OF HOLE 21.5 (EL. -52.0)				18. TOTAL CORE RECOVERY FOR BORING 0			
				19. SIGNATURE OF INSPECTOR BRAD RALPH DRAFTED <input type="checkbox"/> CHECKED <input type="checkbox"/> BCR BCR			
ELEVATION <small>a</small>	DEPTH <small>b</small>	LEGEND <small>c</small>	CLASSIFICATION OF MATERIALS (Description) <small>d</small>	% CORE RECOVERY OR W.C. <small>e</small>	BOX OR SAMPLE NO. <small>f</small>	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) <small>g</small>	
-30.5	0.0	• • • • •	(SP) White medium to fine SAND, some shell	99% RECOV	S-1	LAB: (SP), 2% FINES (FINER THAN #200 SIEVE)	
-34.1	3.6	• • • • •	(SP to CL) White fine SAND into gray fine sandy CLAY		X		
-34.8	4.3	• • • • •			X		
	6.0	• • • • •	(SP-SM) Gray medium to fine SAND		S-2	LAB: (SP), 4% FINES	
-39.0	8.5	• • • • •			S-3	LAB: (SP), 6% FINES	
	9.0	• • • • •	(SP) Gray medium to fine SAND		S-4	LAB: (SM), 23% FINES	
-42.0	11.5	• • • • •			S-5	LAB: (CH), 63% FINES	
	12.0	• • • • •	(SM) Gray to orange silty fine SAND		S-6	LAB: (SC), 41% FINES	
-43.7	13.2	• • • • •			S-7		
	15.0	• • • • •	(CL) Gray CLAY, trace sand		S-8	LAB: (SP-SM), 5% FINES	
-46.7	16.2	• • • • •					
	18.3	• • • • •	(SC) Gray clayey medium to fine SAND				
-48.8	19.6	• • • • •					
	20.1	• • • • •	(CL) Gray medium to fine sandy CLAY				
-50.1	20.6	• • • • •	(SC) Gray clayey medium to fine SAND				
-50.6	21.0	• • • • •	(CL) Gray medium to fine sandy CLAY				
-51.1		• • • • •	(SP) Tan medium to fine SAND				
-51.5		• • • • •					

ENG FORM 1836
(CADD Facsimile)

PROJECT **BAY CO FL OFFSHORE
PANAMA CITY BEACHES NOURISHMENT**

HOLE NO. **V-25-94**

