

Boring Designation WA-29

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1	
						OF 1 SHEETS	
1. PROJECT				9. SIZE AND TYPE OF BIT			
Walton County Borrow Area A							
Walton County, Florida				10. COORDINATE SYSTEM/DATUM		HORIZONTAL	VERTICAL
				Florida State Plane North		NAD 1983	NAVD 88
2. BORING DESIGNATION		LOCATION COORDINATES		11. MANUFACTURER'S DESIGNATION OF DRILL			
WA-29		X = 1,383,230 Y = 477,449		Vibracore			
				<input type="checkbox"/> AUTO HAMMER			
				<input type="checkbox"/> MANUAL HAMMER			
3. DRILLING AGENCY		CONTRACTOR FILE NO.		12. TOTAL SAMPLES		DISTURBED	UNDISTURBED (UD)
4. NAME OF DRILLER				13. TOTAL NUMBER CORE BOXES			
Alpine							
5. DIRECTION OF BORING		DEG. FROM VERTICAL	BEARING	14. ELEVATION GROUND WATER			
<input checked="" type="checkbox"/> VERTICAL							
<input type="checkbox"/> INCLINED				15. DATE BORING		STARTED	COMPLETED
				08-28-06 13:17		08-28-06 13:20	
6. THICKNESS OF OVERBURDEN		0.0 Ft.		16. ELEVATION TOP OF BORING		-70.1 Ft.	
7. DEPTH DRILLED INTO ROCK		0.0 Ft.		17. TOTAL RECOVERY FOR BORING		18 Ft.	
8. TOTAL DEPTH OF BORING		18.0 Ft.		18. SIGNATURE AND TITLE OF INSPECTOR			

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-70.1	0.0					
			Medium sand. Burrows at depth of 6.8' to 7.8', 8.2' to 9.8', and 10.8' to 12'. Shells at 4.5', 7.3' to 8.2'. Scattered organics at depth of 10.5' to 13.5', (SP).		WA-29 0'	Sample #WA-29 0', Depth = 0.0'
					WA-29 1.5'	Sample #WA-29 1.5', Depth = 1.5'
					WA-29 3.0'	Sample #WA-29 3.0', Depth = 3.0'
					WA-29 4.5'	Sample #WA-29 4.5', Depth = 4.5'
					WA-29 6.0'	Sample #WA-29 6.0', Depth = 6.0'
					WA-29 7.5'	Sample #WA-29 7.5', Depth = 7.5'
					WA-29 9.0'	Sample #WA-29 9.0', Depth = 9.0'
-83.6	13.5					
			Carbonate-cemented sediment..			
-88.1	18.0					
			End of Boring			