

DRILLING LOG		DIVISION <b>SOUTH ATLANTIC</b>		Hole No. <b>V-4-94</b>		INSTALLATION <b>MOBILE DISTRICT</b>		SHEET <b>1</b> OF <b>1</b> SHEETS	
1. PROJECT <b>BAY COUNTY OFFSHORE PANAMA CITY BEACHES NOURISHMENT</b>				10. SIZE AND TYPE OF BIT <b>3.5" x 25' VIBRACORE</b>					
2. LOCATION (Coordinates or Station) <b>ZONE FLN: N 459701 E 1533087</b>				11. ELEVATION DATUM <b>NGVD, FOOT U.S.</b>					
3. DRILLING AGENCY <b>TET, INC.</b>				12. MANUFACTURER'S DESIGNATION OF DRILL <b>VIBRACORE</b>					
4. HOLE NO. (As shown on drawing title and file number) <b>V-4-94</b>				13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN		DISTURBED <b>5</b>		UNDISTURBED <b>0</b>	
5. NAME OF DRILLER <b>CHARLIE WESTON</b>				14. TOTAL NUMBER CORE BOXES <b>0</b>					
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED    DEG. FROM VERTICAL				15. ELEVATION GROUNDWATER					
7. THICKNESS OF OVERBURDEN <b>-</b>				16. DATE HOLE		STARTED <b>29 NOV 94</b>		COMPLETED <b>29 NOV 94</b>	
8. DEPTH DRILLED INTO ROCK <b>-</b>				17. ELEVATION TOP OF HOLE <b>EL. -40.3</b>					
9. TOTAL DEPTH OF HOLE <b>15.0 (EL. -55.3)</b>				18. TOTAL CORE RECOVERY FOR BORING <b>0</b>					
				19. SIGNATURE OF INSPECTOR <b>BRAD RALPH</b> DRAFTED <input type="checkbox"/> CHECKED <input type="checkbox"/> <b>DWO   BCR</b>					
ELEVATION <small>a</small>	DEPTH <small>b</small>	LEGEND <small>c</small>	CLASSIFICATION OF MATERIALS (Description) <small>d</small>	% CORE RECOVERY OR W.C. <small>e</small>	BOX OR SAMPLE NO. <small>f</small>	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) <small>g</small>			
<b>-40.3</b>	<b>0.0</b>		(SP) White medium to fine SAND, trace shell		<b>S-1</b>	LAB: (SP), 3% FINES (FINER THAN #200 SIEVE)			
<b>-41.3</b>	<b>1.0</b>		(SM) Brown silty medium to fine SAND		<b>S-2</b>	LAB: (SP-SM), 9% FINES			
<b>-43.1</b>	<b>2.8</b>								
	<b>6.0</b>		(SP) White, tan and gray medium to fine SAND	<b>100% RECOV</b>	<b>S-3</b>	LAB: (SP), 2% FINES			
	<b>9.0</b>								
<b>-52.1</b>	<b>11.8</b>				<b>S-4</b>	LAB: (SP-SM), 5% FINES			
			(SP-SM) Gray medium to fine SAND		<b>S-5</b>	LAB: (SP-SM), 8% FINES			
<b>-55.3</b>	<b>15.0</b>								
						<b>B.O.H.</b>			