

DRILLING LOG		DIVISION <b>SOUTH ATLANTIC</b>		INSTALLATION <b>MOBILE DISTRICT</b>		Hole No. <b>S-28-94</b> SHEET <b>1</b> OF <b>1</b> SHEETS	
1. PROJECT <b>BAY COUNTY OFFSHORE PANAMA CITY BEACHES NOURISHMENT</b>				10. SIZE AND TYPE OF BIT <b>4" DIA. DRILL BIT</b>			
2. LOCATION (Coordinates or Station) <b>ZONE FLN: N 452188 E 1548876</b>				11. ELEVATION DATUM <b>NGVD, FOOT U.S.</b>			
3. DRILLING AGENCY <b>TET, INC.</b>				12. MANUFACTURER'S DESIGNATION OF DRILL <b>SIMCO TR-1 4000</b>			
4. HOLE NO. (As shown on drawing title and file number) <b>S-28-94</b>				13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN <b>8</b>		DISTURBED <b>3</b>	
5. NAME OF DRILLER <b>CHARLIE WESTON</b>				14. TOTAL NUMBER CORE BOXES <b>0</b>			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED    DEG. FROM VERTICAL				15. ELEVATION GROUNDWATER			
7. THICKNESS OF OVERBURDEN <b>-</b>				16. DATE HOLE STARTED <b>1 DEC 94</b> COMPLETED <b>1 DEC 94</b>			
8. DEPTH DRILLED INTO ROCK <b>-</b>				17. ELEVATION TOP OF HOLE <b>EL. -30.3</b>			
9. TOTAL DEPTH OF HOLE <b>16.5 (EL. -46.8)</b>				18. TOTAL CORE RECOVERY FOR BORING <b>0</b>			
				19. SIGNATURE OF INSPECTOR <b>BRAD RALPH</b> DRAFTED <b>DWO</b> CHECKED <b>BCR</b>			
ELEVATION <small>a</small>	DEPTH <small>b</small>	LEGEND <small>c</small>	CLASSIFICATION OF MATERIALS (Description) <small>d</small>	% CORE RECOVERY OR W.C. <small>e</small>	BOX OR SAMPLE NO. <small>f</small>	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) <small>g</small> SPT BLOWS/FT	
-30.3	0.0	• • • • •	(SP) White fine SAND		S-1	LAB: (SP), 2% FINES (FINER THAN #200 SIEVE)    14	
-32.6	2.3	• • • • •			X		
	3.0	• • • • •	(SM) Brown silty fine SAND		S-2	LAB: (SP-SM), 5% FINES    18	
-35.6	5.3	• • • • •			TUBE T-1	LAB: (SP), 5% FINES, 123.6 PCF WET DENSITY @ 22.4% MC, 101.0 DRY DENSITY	
	6.0	• • • • •	(SP-SM) Brown fine SAND		S-3	LAB: (SP-SM), 8% FINES    16	
-38.6	8.3	• • • • •			X		
	9.0	• • • • •			S-4	LAB: (SC), 22% FINES    4	
	12.0	• • • • •	(ML) Gray SILT, trace sand		S-5	LAB: (SC), 30% FINES    4	
	15.0	• • • • •			S-6	LAB: (SC), 45% FINES    WOH	
		• • • • •			S-7	LAB: (CH), 72% FINES    7	
-46.8	16.5	• • • • •			S-8	LAB: (CH), 74% FINES    9	
						B.O.H.	