

# Boring Designation SK-Area3-V02

<b>DRILLING LOG</b>		DIVISION Humiston & Moore Engineers		INSTALLATION Naples, FL		SHEET 1 OF 1 SHEETS	
1. PROJECT Sarasota County Public Works South Siesta Key Beach Restoration Project				9. SIZE AND TYPE OF BIT 3.0 In.			
2. BORING DESIGNATION SK-AREA3-V02				10. COORDINATE SYSTEM/DATUM Florida State Plane West		HORIZONTAL NAD 1983	
3. DRILLING AGENCY Athena Technologies, Inc.				11. MANUFACTURER'S DESIGNATION OF DRILL		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER P. McClellan				12. TOTAL SAMPLES 2		DISTURBED UNDISTURBED (UD)	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				13. TOTAL NUMBER CORE BOXES		14. ELEVATION GROUND WATER -0.5 Ft.	
6. THICKNESS OF OVERBURDEN 0.0 Ft.				15. DATE BORING		STARTED 01-14-14 15:15	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				16. ELEVATION TOP OF BORING -34.8 Ft.		COMPLETED 01-14-14 15:30	
8. TOTAL DEPTH OF BORING 12.0 Ft.				17. TOTAL RECOVERY FOR BORING 10.3 Ft.		18. SIGNATURE AND TITLE OF INSPECTOR A. Freeze	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS	
-34.8	0.0						0
-39.5	4.7		SHELL, medium sand size, little fine quartz sand, poorly graded, subangular, dark gray (5Y-4/1), (SP).		A3-V2-1	Sample #A3-V2-1, Depth = 0.0' - 4.7' Mean (mm): 0.45, Phi Sorting: 1.10 Carbonate: 84.8%, Fines (230): 1.58% (SP)	
-43.7	8.9		Silty fine quartz SAND, little silt, few fine sand size shell, subangular, bioturbated, silt percentage increases with depth, light olive gray (5Y-6/2), (SM).		A3-V2-2	Sample #A3-V2-2, Depth = 4.7' - 8.9' Mean (mm): 0.17, Phi Sorting: 1.46 Shell: 11%, Fines (230): 13.63% (SM)	5
-45.1	10.3		Silty fine quartz SAND, some coarse sand to fine gravel size shell, little silt, subangular, olive gray (5Y-5/2), (SM).				10
			End of Boring				15

FLORIDA DEP ROSS SIESTA KEY 2-27-14.GPJ FL DEP ROSS.GDT 2/27/14