

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Gulf County Supplemental Port St. Joseph, Florida			9. SIZE AND TYPE OF BIT 2.0 In.	
2. BORING DESIGNATION C-501			10. COORDINATE SYSTEM/DATUM Florida State Plane North	
LOCATION COORDINATES X = 1,672,624.38 Y = 250,326.95			HORIZONTAL NAD 1983	
3. DRILLING AGENCY			11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
CONTRACTOR FILE NO.			12. TOTAL SAMPLES DISTURBED UNDISTURBED (UD)	
4. NAME OF DRILLER Athena			13. TOTAL NUMBER CORE BOXES	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			14. ELEVATION GROUND WATER	
DEG. FROM VERTICAL			15. DATE BORING STARTED COMPLETED 07-26-06 07-26-06	
BEARING			16. ELEVATION TOP OF BORING -36.7 Ft.	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			17. TOTAL RECOVERY FOR BORING 12.5 Ft.	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist	
8. TOTAL DEPTH OF BORING 13.0 Ft.				

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-36.7	0.0					
		•••••	Fine grained quartz sand. Abrupt contact, white (10YR-8/1), (SP).		1	Sample #1, Depth = 0.5' - 0.8'
		•••••			2	Sample #2, Depth = 4.0' - 4.3'
		•••••			3	Sample #3, Depth = 5.5' - 5.8'
-43.8	7.1	•••••			4	Sample #4, Depth = 7.5' - 7.8'
-45.5	8.8	•••••	Muddy fine grained quartz sand. Abrupt contact, gray (10YR-6/1), (SP-SM).			
		•••••	Interbedded mud and fine grained quartz sand, light gray (10YR 7/1) to, dark gray (10YR-4/1), (SM).			
-49.2	12.5	•••••	End of Boring			

FLORIDA DEP ROSS GULF COUNTY SUPPLEMENTAL.GPJ FL DEP ROSS.GDT 12/5/07