

Boring Designation C-201

| | | | | |
|--|--|-----------------|---|--------------------------------------|
| DRILLING LOG | | DIVISION | INSTALLATION | SHEET 1 OF 1 SHEETS |
| 1. PROJECT Gulf County Supplemental Port St. Joseph, Florida | | | 9. SIZE AND TYPE OF BIT 2.0 In. | |
| 2. BORING DESIGNATION C-201 | | | 10. COORDINATE SYSTEM/DATUM Florida State Plane North | |
| LOCATION COORDINATES X = 1,673,713.23 Y = 262,930.34 | | | HORIZONTAL NAD 1983 | |
| 3. DRILLING AGENCY | | | 11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER | |
| CONTRACTOR FILE NO. | | | 12. TOTAL SAMPLES | |
| 4. NAME OF DRILLER Athena | | | 13. TOTAL NUMBER CORE BOXES | |
| 5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | | | 14. ELEVATION GROUND WATER | |
| DEG. FROM VERTICAL | | | 15. DATE BORING STARTED 07-24-06 COMPLETED 07-24-06 | |
| BEARING | | | 16. ELEVATION TOP OF BORING -36.2 Ft. | |
| 6. THICKNESS OF OVERBURDEN 0.0 Ft. | | | 17. TOTAL RECOVERY FOR BORING 10 Ft. | |
| 7. DEPTH DRILLED INTO ROCK 0.0 Ft. | | | 18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist | |
| 8. TOTAL DEPTH OF BORING 11.0 Ft. | | | | |

| ELEV. (ft) | DEPTH (ft) | LEGEND | CLASSIFICATION OF MATERIALS Depths and elevations based on measured values | % REC. | BOX OR SAMPLE | REMARKS |
|------------|------------|--------|---|--------|---------------|--------------------------------|
| -36.2 | 0.0 | | | | | |
| | | | Fine grained quartz sand with trace mud-filled burrows. Thin mud layer from 5.6'-5.8'. Lightening in color with depth, very pale brown (10YR 8/2) to, white (10YR-8/1), (SP). | | 1 | Sample #1, Depth = 0.5' - 0.8' |
| | | | | | 2 | Sample #2, Depth = 4.0' - 4.3' |
| | | | | | 3 | Sample #3, Depth = 6.0' - 6.3' |
| | | | | | 4 | Sample #4, Depth = 9.0' - 9.3' |
| -46.2 | 10.0 | | End of Boring | | | |

FLORIDA DEP ROSS GULF COUNTY SUPPLEMENTAL.GPJ FL DEP ROSS.GDT 12/5/07