

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Gulf County Supplemental Port St. Joseph, Florida			9. SIZE AND TYPE OF BIT 2.0 In.	
2. BORING DESIGNATION C-403			10. COORDINATE SYSTEM/DATUM Florida State Plane North	
LOCATION COORDINATES X = 1,678,483.75 Y = 254,360.			HORIZONTAL NAD 1983	
3. DRILLING AGENCY			11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
CONTRACTOR FILE NO.			12. TOTAL SAMPLES	
4. NAME OF DRILLER Athena			13. TOTAL NUMBER CORE BOXES	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			14. ELEVATION GROUND WATER	
DEG. FROM VERTICAL			15. DATE BORING	
BEARING			STARTED 07-26-06	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			16. ELEVATION TOP OF BORING -36.4 Ft.	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			17. TOTAL RECOVERY FOR BORING 11.2 Ft.	
8. TOTAL DEPTH OF BORING 12.0 Ft.			18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-36.4	0.0					
-40.4	4.0		Fine grained quartz sand with trace mud-filled burrows. Abrupt contact, white (10YR-8/1), (SP).		1	Sample #1, Depth = 0.5' - 0.8'
-42.9	6.5		Muddy fine grained quartz sand with abundant fine grained quartz sand-filled burrows, dark gray (10YR 4/1) to, light gray (10YR-7/1), (SM).		2	Sample #2, Depth = 4.5' - 4.8'
-47.6	11.2		Muddy, peaty, organic-rich fine grained quartz sand. Wood from 9' to 9.4'. Mottled with fine grained quartz sand-filled burrows, very dark gray (10YR-3/1), (SM).			
			End of Boring			

FLORIDA DEP ROSS GULF COUNTY SUPPLEMENTAL GPJ FL DEP ROSS.GDT 12/5/07