

Boring Designation PB-95-C44

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT Juno Historic Palm Beach County				9. SIZE AND TYPE OF BIT			
2. BORING DESIGNATION PB-95-C44				10. COORDINATE SYSTEM/DATUM Florida State Plane East		HORIZONTAL NAD 1983	
3. DRILLING AGENCY Olsen Associates Inc				11. MANUFACTURER'S DESIGNATION OF DRILL 4-inch Alpine Pneumatic		VERTICAL NAVD 88	
4. NAME OF DRILLER Alpine Ocean Seismic Survey, Inc.				12. TOTAL SAMPLES		DISTURBED UNDISTURBED (UD)	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				13. TOTAL NUMBER CORE BOXES		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
6. THICKNESS OF OVERBURDEN 0.0 Ft.				14. ELEVATION GROUND WATER		15. DATE BORING 08-08-95	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				16. ELEVATION TOP OF BORING -68.9 Ft.		COMPLETED 08-08-95	
8. TOTAL DEPTH OF BORING 16.7 Ft.				17. TOTAL RECOVERY FOR BORING 16.7 Ft.		18. SIGNATURE AND TITLE OF INSPECTOR	
ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS	
-68.9	0.0						
			Gray, medium-to-fine sand, trace of coarse sand, (SP).		0.5	Sample #0.5, Depth = 0.5' Some coarse shell gravel (20%-35%) at 1.0'-1.9', little fine gravel at 3.9'-5.4'.	
					2.5	Sample #2.5, Depth = 2.5'	
					4.5	Sample #4.5, Depth = 4.5'	
-75.1	6.2						
-76.0	7.1		Brown, medium-to-fine sand, little clay, (SP).		6.5	Sample #6.5, Depth = 6.5'	
			Black-brown, organic clay, (OH).		10.5	Sample #10.5, Depth = 10.5' Zone of fine clayey sand at 10.0'-10.2', followed by zone of shell hash (medium, clean friable, soft) at 10.2'-10.9'. Very peaty from 11.0'-13.8'. Dryer than above.	
-82.7	13.8						
-83.3	14.4		Light brown, fine sand, (SP).		14.5	Sample #14.5, Depth = 14.5'	
			Tan, fine sand, some clay, (SP).		16.5	Sample #16.5, Depth = 16.5'	
-85.6	16.7				Comp	Sample #Comp, Depth = 16.7' Composite	
			End of Boring				