

FROMWELL &  
CARRIER, INC.

# TEST BORING REPORT

HOLE NO. LB-15

PROJECT: LONG BOAT KEY

FILE NO. 8102

CLIENT: ATM

SHEET NO. 1 of 2

CONTRACTOR: TET

LOCATION: \_\_\_\_\_

GROUNDWATER

DEPTH TO:

CASING

SAMPLER

CORE  
BARREL

ELEVATION: \_\_\_\_\_

DATE

TIME

WATER

BOTTOM OF  
CASING

BOTTOM OF  
HOLE

TYPE:

SIZE I.D.:

HAMMER WT.:

HAMMER FALL:

SPT

1 3/8"

140#

30"

DATE START: 2-28-89

DATE FINISH: 2-28-89

DRILLER: JAY

INSPECTOR: MRB

DEPTH

SAMP.  
NO.

CASING  
BLOWS  
PER  
FOOT

SAMPLER  
BLOWS  
PER  
6 INCHES

SPT  
BLOWS  
PER  
FOOT

STRATA  
CHANGE

## FIELD CLASSIFICATION AND REMARKS

WATER DEPTH 23' 4" @ 3:09 PM (START)

WATER DEPTH 23' 5" @ 5:04 PM (FINISH)

5

10

15

20

25

30

1<sub>s</sub>

2

3<sub>s</sub>

2

3

2

2

4

5

4

6

6

4

3

4

6

5

9

7

SP/SM

SP/SM

LOOSE GREY FINE GR. SAND W/TRACE OF SHELL FRAGMENTS. MORE SHELL IN TOP 3".

LOOSE LT. GREY FINE GR. SAND W/SOME SHELL FRAG.

SAME, LT. TAU-GREY

XXXXXXXXXX

BLOWS/FT.

DENSITY

BLOWS/FT.

CONSISTENCY

SAMPLE IDENTIFICATION

0 - 4

VERY LOOSE

0 - 2

VERY SOFT

S \_\_\_\_\_ SPLIT SPOON

4 - 10

LOOSE

2 - 4

SOFT

T \_\_\_\_\_ THIN WALL TUBE

10 - 30

COMPACT/M. DENSE

4 - 8

FIRM

U \_\_\_\_\_ UNDISTURBED PISTON

30 - 50

DENSE

8 - 15

STIFF

O \_\_\_\_\_ OPEN END ROD

50 +

VERY DENSE

15 - 30

VERY STIFF

W \_\_\_\_\_ WASH SAMPLE





